

Market Leading Portfolio of Electric Actuators



FLOCONX[®]
— USA FLOW CONTROL COMPANY —

FLOCONX LLC
USA FLOW CONTROL COMPANY

SALES | INFORMATION
SALES@FLOCONX.COM
VENTAS@FLOCONX.COM

FLOW CONTROL, OUR PASSION.™

WWW.FLOCONX.COM



Product Selection Guide
Bettis™ Electric Actuators



Delivering market leading valve automation for the world's

You need reliable and dependable actuators for your motor operated valves from a market leading partner you can trust.

The electric actuator portfolio from Bettis covers a range of applications, from the latest in intelligent control and fail-safe technology to robust heavy-duty solutions able to withstand the harshest environments.

For decades, Bettis continues to be a single-source provider of field-proven, reliable and safe valve automation solutions—helping companies all over the world in oil and gas, power, chemical, water and wastewater, marine, and subsea.

RTS

Stroke:   

Function:   

Features:

- Highly configurable and intelligent actuator with options for continuous modulation and mechanical fail-safe
- Adjustable operating and fail-safe speed
- Non-intrusive setup via local interface, Bluetooth™, or DCMLink (in development)
- Multi-turn torque up to 64 Nm (47 ft lbs)
- Quarter-turn torque up to 250 Nm (184 ft lbs)
- Linear force up to 25 kN (5,620 lbs)
- Fail-safe quarter-turn torque up to 5,000 Nm (3,687 ft lbs)
- Fail-safe linear force up to 40 kN (8,992 lbs)

Protocols:

- Modbus™, HART™, FOUNDATION Fieldbus™, PROFIBUS™, PROFINET™



XTE3000

Stroke:   

Function:  

Features:

- Intelligent and versatile actuator with a wide range of torque and speed for on/off & control
- Non-intrusive setup via local interface, Bluetooth, or DCMLink
- Multi-turn torque up to 1,440 Nm (1,062 ft lbs)
- Quarter-turn torque up to 63,000 Nm (46,466 ft lbs)
- Couple to available external gears to extend upper limits of torque and thrust

Protocols:

- Modbus, HART, FOUNDATION Fieldbus, PROFIBUS, LonWorks™



Legend:

Stroke:  Multi-turn  Linear  Quarter-Turn **Function:**  Control/Modulating  On/Off  Fail-Safe

toughest automation, safety, and productivity challenges

M2CP

Stroke:



Function:



Features:

- Robust, easy to service, intrusive actuator
- Compatible with DCMLink
- Multi-turn torque up to 21,693 Nm (16,000 ft lbs)
- Quarter-turn torque up to 370,000 Nm (273,000 ft lbs)
- Linear force up to 2,224 kN (500,000 lbs)
- Couple with available external gears for increased torque & thrust range

Protocols:

- Modbus, HART, FOUNDATION Fieldbus, PROFIBUS, DeviceNet™, Ethernet

SCE300

Stroke:



Function:



Features:

- Smart, compact quarter-turn actuator
- Highly configurable with variable speed settings
- Non-intrusive setup via Bluetooth
- Quarter-turn torque from 63 Nm (46 ft lbs) to 2,000 Nm (1,475 ft lbs)

Protocols:

- PROFIBUS, DeviceNet

TorqPlus

Stroke:



Function:



Features:

- Robust, easy to service, intrusive actuator
- Compact design with mechanical fail-safe option
- Quarter-turn torque from 11 Nm (8 ft lbs) to 2,260 Nm (1,667 ft lbs)

Network Controls and Software

Controlinc Network Master



Features:

- Control and monitor up to 250 actuators
- Common functions come pre-configured
- Connect multiple masters to automate 1000+ actuators

Protocols:

- Modbus

DCMLink Software

Features:

- Diagnose, configure, calibrate, and monitor all electric actuators from a central location, independent of the protocol, actuator, or host system
- Real-time monitoring and control of asset data, profiles, alarm, and event logs
- Integrates with Emerson PlantWeb, AMS Snap-On, and Bluetooth





FLOCONX[®]
— USA FLOW CONTROL COMPANY —

FLOCONX LLC
USA FLOW CONTROL COMPANY

SALES | INFORMATION
SALES@FLOCONX.COM
VENTAS@FLOCONX.COM

FLOW CONTROL, OUR PASSION.™

WWW.FLOCONX.COM

BETTIS™

The Emerson logo is a trademark and service mark of Emerson Electric Co. © 2019 Emerson Electric Co. Bettis logotype is a registered trademark of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2019 Emerson. All rights reserved.
BRO-02-04-0208-EN-CS / Printed in USA / 05-19



CONSIDER IT SOLVED.™